


CTAF
122.7
HOUSTON DEP CON
134.45 284.0

(HOODO7.HOODO) 21280 AL-6674 (FAA)
HOODO SEVEN DEPARTURE (RNAV)

RWJ AIRPARK (54T)
BAYTOWN, TEXAS

TOP ALTITUDE:
ASSIGNED BY ATC

- NOTE: RNAV 1.
- NOTE: RADAR required.
- NOTE: ATC assigned only.
- NOTE: DME/DME/IRU or GPS required.
- NOTE: For non-GPS equipped aircraft, LCH, LLA, TBD, and LEV DME's must be operational.



TAKEOFF MINIMUMS
Rwys 14, 32: NA - Environmental.
Rwys 8, 26: Standard with minimum
climb of 500' per NM to 540.

SCHOLES
VUH



HOODO
SBIRD
(36)
11000
*1400
087°

CFOOD

(60)

BOWFN

(60)

LEEVILLE
LEV

11000
*1700
076°

1000
*1000
048°
1812

HARVEY
HRV

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 8: Climb on heading 084° to 540, for RADAR vectors to VUH VOR/DME, thence . . .
TAKEOFF RUNWAY 26: Climb on heading 264° to 540, for RADAR vectors to VUH VOR/DME, thence . . .

. . . on track 118° to HOODO, then on (transition). Maintain ATC assigned altitude.
Expect filed altitude 10 minutes after departure.

- BOWFN TRANSITION (HOODO7.BOWFN)
- CFOOD TRANSITION (HOODO7.CFOOD)
- HARVEY TRANSITION (HOODO7.HRV)
- LEEVILLE TRANSITION (HOODO7.LEV)
- SBIRD TRANSITION (HOODO7.SBIRD)