

WAAS CH 72921 W17A	APP CRS 174°	Rwy Idg TDZE 994 Apt Elev 1002
--	------------------------	--

RNAV (GPS) RWY 17

PERRY MUNI (F22)



RNP APCH.

NA

Baro-VNAV NA when using KPNC altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When VGSI inop, procedure NA at night. Rwy 17 helicopter visibility reduction below 1 SM NA. Obtain local altimeter setting on CTAF; when not received, use Ponca City altimeter setting and increase all DA 53 feet, all MDA 60 feet and increase LNAV/VNAV all Cats and LNAV Cat C visibility ¼ mile.


MISSED APPROACH: Climb to 3000 direct HIGHY and on track 192° to YUPUD and hold.

KANSAS CITY CENTER 127.8 319.1	UNICOM 122.8 (CTAF) 0
--	---------------------------------



Procedure NA for arrivals at GULLI on V140 eastbound.

4 NM Holding Pattern		AHOBY	*LNAV only	3000	HIGHY	tr 192°	YUPUD
3000 ← 354°		174° →	174°	2600	CUXOP 1.6 NM to RW17	*1520	
GP 3.00° TCH 37°		6 NM	3.4 NM	1.6			
CATEGORY	A	B	C	D			
LPV DA	1244-1		250 (300-1)		NA		
LNAV/VNAV DA	1434-1½		440 (500-1½)		NA		
LNAV MDA	1360-1		366 (400-1)	1360-1⅛	366 (400-1⅛) NA		



SC-1, 27 NOV 2025 to 25 DEC 2025

SC-1, 27 NOV 2025 to 25 DEC 2025