

WAAS CH 78202 W11A	APP CRS 110°	Rwy Idg TDZE Apt Elev	5000 2537 2537
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 11

NAMPA MUNI (MAN)


▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). When Circling to Rwy 29 at night, operational VGSI required, remain on or above VGSI glidepath until threshold. DME/DME RNP-0.3 NA. Rwy 11 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 5100 direct NEMEW and hold, continue climb-in-hold to 5100.

AWOS-3 118.325	BIG SKY APP CON 119.6 269.4	UNICOM 122.7 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------



ELEV 2537

TDZE 2537

MIRL Rwy 11-29 0

5 NM Holding Pattern 5100 ← 289° → 109° → 4200 GP 3.00° TCH 40				5100 NEMEW *LNAV only			
ZURMU				YEPDU			
5 NM				4200			
109°				110°			
7.9 NM				3.4 NM			
CUSMU				1.7 NM to RW11			
*1.1 NM to RW11				*3100			
0.6 NM				1.1 NM			
RW11							
CATEGORY	A		B		C		D
LPV DA	2787-7/8		250 (300-7/8)				
LNAV/VNAV DA	2851-1		314 (400-1)				
LNAV MDA	2920-1		383 (400-1)		2920-1 1/8		383 (400-1 1/8)
CIRCLING	3060-1		523 (600-1)		3100-1 1/2		3220-2 1/4
					563 (600-1 1/2)		683 (700-2 1/4)