

LOC/DME I-TDF
108.7
Chan **24**

APP CRS
060°

Rwy Idg **5702**
TDZE **604**
Apt Elev **609**

ILS or LOC RWY 6

RALEIGH RGNL AT PERSON COUNTY (TDF)

▼

For inop ALS, increase S-LOC 6 visibility Cats C/D to 1½ SM and increase FIPR fix minimums S-LOC 6 visibility Cats C/D to 1 SM.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 on heading 021° and on RDU VORTAC R-356 to ALDAN INT/RDU 32.3 DME and hold, continue climb-in-hold to 3000.

AWOS-3 126.725	RALEIGH APP CON 132.35 256.9	GCO 119.7	UNICOM 122.7 (CTAF) 0
--------------------------	--	---------------------	---------------------------------

CATEGORY	A	B	C	D
S-ILS 6	804-½ 200 (200-½)			
S-LOC 6	1220-½	616 (700-½)	1220-1⅜	616 (700-1⅜)
CIRCLING	1220-1	611 (700-1)	1300-2	1300-2¼
			691 (700-2)	691 (700-2¼)
FIPR FIX MINIMUMS				
S-LOC 6	980-½	376 (400-½)	980-⅝	376 (400-⅝)
CIRCLING	1080-1	471 (500-1)	1300-2	1300-2¼
			691 (700-2)	691 (700-2¼)

ELEV 609

TDZE 604

REIL Rwy 24 0

MIRL Rwy 6-24 0

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

ROXBORO, NORTH CAROLINA

RALEIGH RGNL AT PERSON COUNTY (TDF)

ILS or LOC RWY 6

Amdt 2A 05OCT23

36°17'N-78°59'W