

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Inop table does not apply.

ALSF-2

MISSED APPROACH: Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

ORLANDO APP CON 134.95 281.425	NASA TOWER ★ 128.55 (CTAF) 284.0	GND CON 121.75
--	--	--------------------------

RADAR REQUIRED

Approach path: ROCIT (IF) → STARS (FAF) → RW15. Altitudes: 2500, 1500, 105 ±, 508, 582, 397. Distances: 9 NM, 2500 (6), 1500 (6), 105 ±, 508, 582, 397. Radar: R-2935, R-2934, R-2932, R-2933. MSA RW15 25 NM (3000). CAPE CANAVERAL SFS SKID STRIP.

ROCIT

2500

GP 3.00°
TCH 55

STARS

1500

RW15

800

2500

EARTH

*0.9 NM to RW15

*LNAV only

6.1 NM

3.6 NM

0.9 NM

CATEGORY	A	B	C	D	E
LPV DA		208-1	200 (200-1)		
LNAV/VNAV DA		286-1	278 (300-1)		
LNAV MDA		360-1	352 (400-1)		
CIRCLING	420-1 411 (500-1)	460-1 451 (500-1)	940-2¾ 931 (1000-2¾)	940-3	931 (1000-3)

ELEV 9, TDZE 8. Missed approach: Climb to 800, then climbing left turn to 2500 direct EARTH and hold. HIRL Rwy 15-33.

TITUSVILLE, FLORIDA
Amdt 1A 25MAY17

SPACE FLORIDA LAUNCH AND LANDING FACILITY (TTS)
28°37'N-80°42'W

RNAV (GPS) RWY 15