

WAAS

CH **69318**

W30A

APP CRS

296°

Rwy Idg

5650

TDZE

2131

Apt Elev

2135

RNAV (GPS) RWY 30

WATFORD CITY MUNI (S25)

RNP APCH - GPS.

⚠

VDP NA when using Williston altimeter setting. When local altimeter setting not received, use Williston Basin Int altimeter setting: increase LPV DA to 2488 feet; all visibility ¼ SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH: Climb to 4500 direct GERHE and hold.

AWOS-3PT 118.125	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------

ELEV 2135

D

TDZE 2131

4500

GERHE

△

BOWIS

4100

△

CIPGO

4100

△

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 45).

5 NM Holding Pattern

1.6 NM to RW30

1.6

4.5 NM

4.1 NM

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	2381-3¼ 250 (300-¾)			
LNAV MDA	2680-1	549 (600-1)	2680-1½	549 (600-1½)
C CIRCLING	2700-1 565 (600-1)	2760-1 625 (700-1)	2760-1¾ 625 (700-1¾)	2960-2¾ 825 (900-2¾)

WATFORD CITY, NORTH DAKOTA

Amdt 1A 03NOV22

47°48'N-103°15'W

WATFORD CITY MUNI (S25)

RNAV (GPS) RWY 30