

APP CRS
130°

Rwy Ldg
TDZE
408

Apt Elev
412

RNAV (GPS) RWY 13
FRANKLIN COUNTY (F53)

▼

NA

DME/DME RNP-0.3 NA. Use Mount Pleasant Rgnl altimeter setting; if not received, procedure NA. Procedure NA at night. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 3000 direct FOSMA and hold.

OSA AWOS-3 119.775	FORT WORTH CENTER 132.025 317.75	UNICOM 123.0 (CTAF)
-----------------------	-------------------------------------	------------------------

The main chart displays the RNAV (GPS) RWY 13 approach. Key features include:

- Initial Descent:** From 3000 MSL, a 3° descent angle leads to a 130° turn at 3100 MSL (5.7 NM from start).
- Intermediate Descent:** A 3° descent angle leads to a 310° turn at 2000 MSL (16.2 NM from start).
- Final Descent:** A 3° descent angle leads to the runway at 412 MSL (36.0 NM from start).
- Navigation Aids:** IAF PARIS PRX, IAF DUYAD, (IF/IAF) KEDEY, (FAF) ICUKA, and FOSMA are marked.
- Obstacles:** JAXAB (3000 MSL, 360°), OSUYE (3000 MSL, 290°), and LENYI (3000 MSL, 235°) are shown.
- MSA:** MSA RW 13 25 NM with a 2600 MSL ceiling.

ELEV 412 TDZE 408

130°

0.43° UP

3000 X 40

436

MIRL Rwy 13-31

5 NM Holding Pattern

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 37).

3000

310°

130°

KEDEY

ICUKA

2000

3.04°

TCH 40

6.2 NM

4.9 NM

RW13

FOSMA

4 NM

131°

311°

CATEGORY	A	B	C	D
LNAV MDA	820-1 412 (500-1)		NA	
CIRCLING	940-1 528 (600-1)	980-1 568 (600-1)		NA

MOUNT VERNON, TEXAS
Orig-B 25MAR21

33°13'N-095°14'W

FRANKLIN COUNTY (F53)
RNAV (GPS) RWY 13