

WAAS CH 63214 W18A	APP CRS 175°	Rwy Idg 5200 TDZE 718 Apt Elev 733
--	------------------------	---

RNAV (GPS) RWY 18


CLAREMORE RGNL (GCM)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV Cats A/B visibility to 1½ SM.

ODALS

MISSED APPROACH: Climb to 2400 direct DAVLE and hold.

AWOS-3PT 119.925	TULSA APP CON 119.1 360.825	UNICOM 122.7 (CTAF) 0
----------------------------	---------------------------------------	---------------------------------



4 NM Holding Pattern		CAMOB		CUMOL		HEGLI 2.3 NM to RW18		2400	DAVLE
2500 ← 355°		175° →		175°		*1.4 NM to RW18		*LNAV only.	
GP 3.00° TCH 43		2400		*1460		RW18			
		6.1 NM		2.9 NM		0.9 NM		1.4 NM	
CATEGORY	A	B		C		D			
LPV DA	968-¾		250 (300-¾)		NA				
LNAV/VNAV DA	1281-1½		563 (600-1½)		NA				
LNAV MDA	1200-¾		482 (500-¾)		1200-1¼		482 (500-1¼)		NA
CIRCLING	1260-1		527 (600-1)		1380-1¾		647 (700-1¾)		NA

