WAAS CH 42741 W11A	APP CRS 111°	Rwy ldg 4982 TDZE 128 Apt Elev 128

RNAV (GPS) RWY 11
ST GEORGE (PBV) (PAPB)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 47°C (117°F). DME/DME RNP-0.3 NA. Circling NA north of Rwy 11-29. Inop table does not apply to LPV all Cats and LNAV Cat A. For inop ALS, increase LNAV/VNAV all Cats visibility to 2½ SM. For inop ALS, increase LNAV Cat C visibility to 2½ SM.

MALSF

MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct OSUCA and hold.

ASOS	ANCHORAGE CENTER	CTAF
135.45	119.1 339.8	122.8 L





CATEGORY	A	B	C	D
LPV DA	428-1 300 (300-1)			NA
LNAV/VNAV DA	957-2 829 (900-2)			NA
LNAV MDA	900-1 772 (800-1)		900-2 772 (800-2)	NA
C CIRCLING	900-1 772 (800-1)	980-1¼ 852 (900-1¼)	980-2½ 852 (900-2½)	NA

AK, 27 NOV 2025 to 22 JAN 2026

AK, 27 NOV 2025 to 22 JAN 2026