

EC-3, 27 NOV 2025 to 25 DEC 2025

WAAS
CH 62937
W09A

APP CRS
091°

Rwy Ldg
TDZE 735
Apt Elev 738

AL-9195 (FAA)

25275

RNAV (GPS) RWY 9

RANTOUL NTL AVN CNTR-FRANK ELLIOTT FLD (TIP)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F).
DME/DME RNP-0.3 NA. When local altimeter setting not received, use Champaign Urbana altimeter setting and increase DA 41 feet and all MDA 60 feet; increase LNAV/VNAV all Cats and LNAV Cats C/D visibility 1/8 mile and Circling Cats C/D visibility 1/4 mile. Baro-VNAV and VDP NA when using Champaign Urbana altimeter setting. Helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH:
Climb to 3000 direct
MEDLE and hold.

AWOS-3
119.025

CHAMPAIGN APP CON ★
121.35 285.65

UNICOM
123.0 (CTAF) 0

(IF/IAF)
LEVVI

2300
090°
(6.2)

091°
(FAF)
RATUE

RW09

MEDLE

4 NM

090°
270°

4 NM

091°
271°

3100
180°
30 NM
LEVVI (NoPT)

3000
180°
30 NM
LEVVI

360°
360°

4 NM
Holding Pattern

LEVVI

3000

270°
090°

GP 3.00°
TCH 40

RATUE

2300

091°

RW09

3000

MEDLE

*1.6 NM to RW09

*LNAV only.

6.2 NM

3.2 NM

1.6 NM

CATEGORY	A	B	C	D
LPV DA	985-1 250 (300-1)			
LNAV/VNAV DA	1167-1½ 432 (500-1½)			
LNAV MDA	1280-1 545 (600-1)		1280-1½ 545 (600-1½)	
CIRCLING	1280-1 542 (600-1)		1380-1¾ 642 (700-1¾) 1420-2¼ 682 (700-2¼)	

REIL Rwy 9 and 27 0

MIRL Rwy 9-27 and 18-36 0

ELEV 738

TDZE 735

81

75

4894

5001 X 75

36

091°

27

RANTOUL, ILLINOIS

40°18'N-88°09'W

RANTOUL NTL AVN CNTR-FRANK ELLIOTT FLD (TIP)

RNAV (GPS) RWY 9

EC-3, 27 NOV 2025 to 25 DEC 2025