


WAAS CH 61108 W21A	APP CRS 212°	Rwy Idg 4000 TDZE 217 Apt Elev 220
--	------------------------	---

RNAV (GPS) RWY 21

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 48°C (118°F). Helicopter visibility reduction below $\frac{3}{4}$ SM NA. DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3000 direct ECAGU and via 164° track to HISOB and hold.

AWOS-3P 135.75	ANCHORAGE CENTER 127.0 290.2	FAIRBANKS RADIO 122.4	UNICOM 122.8 (CTAF) ①
--------------------------	--	---------------------------------	---------------------------------



3000 ↑	ECAGU ✱	tr 164°	HISOB △	VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.00/TCH 25).			
CATEGORY		A		B		C	
LPV	DA	517-1 300 (300-1)					
RNAV/ VNAV	DA	549-1¼ 332 (400-1¼)					
RNAV	MDA	540-1 323 (400-1)					
CIRCLING		600-1 380 (400-1)		680-1 460 (500-1)		680-1½ 460 (500-1½)	
						780-2 560 (600-2)	

