

WAAS
CH **58033**
W16A

APP CRS
159°

Rwy Ldg
TDZE **1368**
Apt Elev **1368**

RNAV (GPS) RWY 16

WADENA MUNI (ADC)

⚠

DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. VDP and Baro-VNAV NA with Staples altimeter setting. When local altimeter setting not received, use Staples altimeter setting and increase all DA 52 feet and all MDA 60 feet, increase LNAV/VNAV visibility 1/8 mile, LNAV Cat C visibility 1/4 mile and Circling Cat C visibility 1/4 mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (1°F) or above 54°C (130°F).

MISSED APPROACH:

Climb to 3300 direct JOLIT and hold.

AWOS-3PT
118.875

MINNEAPOLIS CENTER
126.1 269.2

GCO
121.725

UNICOM
122.8 (CTAF) 0

4 NM Holding Pattern WENVI		3300	JOLIT	*LNAV only	
3300 ← 339°		159° →	159°	3000	
GP 3.00° TCH 42				DIXGY 3000	ZOBED 1.8 NM to RW16
				*1980	*1.1 NM to RW16
				8 NM	3.2 NM 0.7 1.1 NM
CATEGORY	A	B	C	D	
LPV DA	1631-1		263 (300-1)	NA	
LNAV/VNAV DA	1767-1 3/8		399 (400-1 3/8)	NA	
LNAV MDA	1760-1		392 (400-1)	1760-1 3/8 392 (400-1 3/8)	NA
CIRCLING	1780-1 412 (500-1)	1820-1 452 (500-1)	1940-1 572 (600-1 1/2)	NA	

WADENA, MINNESOTA

Orig-A 02APR15

46°27'N-95°13'W

WADENA MUNI (ADC)

RNAV (GPS) RWY 16