


WAAS CH 61299 W28A	APP CRS 275°	Rwy Ldg TDZE 998 Apt Elev 1026
--	------------------------	--

RNAV (GPS) Y RWY 28
HARTSFIELD/JACKSON ATLANTA INTL (ATL)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 26R or 26L or 27R, or Rwys 26R and 27R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.					ALSIF-2 	MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 direct SCARR and hold.
D-ATIS ARR 119.65 DEP 125.55	ATLANTA APP CON 127.9 379.9	ATLANTA TOWER ALL 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS 119.1 125.325 123.85 119.3 119.5 254.4				GND CON ALL (8L-26R,8R-26L) (9L-27R,9R-27L) 10-28 RWYS 121.9 121.75 121.65 254.4

CINC DEL 118.1	CPDLC
-----------------------------	-------



RADAR REQUIRED

		SCARR
*LNAV only.		
CATEGORY	A	B
LPV DA	1198/18	200 (200-½)
LNAV/VNAV DA	1250/24	252 (300-½)
LNAV MDA	1440/24	442 (500-½)

ELEV 1026	D	TDZE 998
HIRL all Rwys TDZ/CL Rwys 8L, 9R, 10, 26R, 27L and 28		

SE-4, 25 DEC 2025 to 22 JAN 2026

SE-4, 25 DEC 2025 to 22 JAN 2026