


LOC/DME I-AHI	APP CRS	Rwy Ldg
109.1	352°	13500
Chan 28		TDZE 6118
		Apt Elev 6187

ILS or LOC RWY 35R
CITY OF COLORADO SPRINGS MUNI (COS)


⚠ **⚠** RADAR required when R-2601 in use.

MISSED APPROACH: Climb to 6700 then climbing right turn to 9000 on heading 047° and on BRK VOR/DME R-091 to ADANE INT/BRK 11.1 DME and hold.

ATIS 125.0 254.3	SPRINGS APP CON 124.0 257.875	SPRINGS TOWER 119.9 360.6	GND CON 121.7 348.6	CLNC DEL 134.45 363.125
----------------------------	---	-------------------------------------	-------------------------------	-----------------------------------



ELEV 6187	D	TDZE 6118
MIRL Rwy 13-31		
HIRL Rws 17R-35L and 17L-35R		
REIL Rws 13, 17R, 31 and 35R		
TDZ/CL Rws 17L and 35R		



Procedure NA for arrival on PUB VORTAC airway radials 267 CW 354.

IAF PUEBLO 116.7 PUB Chan 114

ALTERNATE MISSED APCH FIX

R-245 354° 174° R-354 112.1 HGO Chan 58

116.7 PUB Chan 114

DRAKE PUB 18.7

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).		6700	9000	ADANE
FALUR INT I-AHI 12.5		CEGIX INT I-AHI 5.9	BRK R-091	△
GS 3.00° TCH 55		8100	8100	I-AHI DME ANTENNA *LOC only
Use I-AHI DME when on the localizer course.		6.6 NM	5.3 NM	0.8 NM
CATEGORY	A	B	C	D
S-ILS 35R	6318/40 200 (200-¾)			
S-LOC 35R	6420/55	302 (300-1)	6420/45	302 (300-¾)
CIRCLING	6740-1 553 (600-1)	6800-1 613 (700-1)	7040-2½ 853 (900-2½)	7260-3 1073 (1100-3)