

WAAS CH 70642 W22D	APP CRS 216°	Rwy Ldg 10000 TDZE 642 Apt Elev 645
--	------------------------	--

RNAV (GPS) Z RWY 22R

DETROIT METRO WAYNE COUNTY (DTW)

RNP APCH.


Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500.

MALSR



MISSED APPROACH: Climb to 1100 then dimbing right turn 4000 direct DOHNT and hold, continue climb in hold to 4000.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 128.125 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	---------------------------------------	---	---------------------------	-------



1100	4000	DOHNT	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/ TCH 71)
*LNAV only.			
RW22R			
GEETR 2000			
NUJNT JOYDD			
TARAH 3000			
GUYVE 4000			
FUDDJ 4000			
GP 3.00° TCH 55'			
CATEGORY	A	B	C
LPV DA	842/18		200 (200-½)
LNAV/VNAV DA	948/24		306 (400-½)
LNAV MDA	1040/24	398 (400-½)	1040/35 398 (400-¾)
CIRCLING	1180-1	535 (600-1)	1180-1½ 535 (600-½) 1240-2 595 (600-2)

