

ATIS 370.925 ★	RADAR required	Rwy	Knots	60	120	180	240	300	360
GND CON 251.15		7 ⑥	V/V(fpm)	276	552	828	1104	1380	1656
NAVY FALLON TOWER ★	TOP ALTITUDE:	13L/R ⑤	V/V(fpm)	211	422	633	844	1055	1266
119.25 340.2									
NAVY FALLON DEP CON ★									
120.85 360.2									


TOP ALTITUDE:
ASSIGNED BY ATC

Minimum Climb Rate
Ⓢ to 5200
Ⓢ to 5400

CAUTION: Fallon Muni Airport (uncontrolled) 5 NM NW pattern alt 800' AGL.

FALLON
Chan 82 NFL

Rwy 7: Do not exceed 270 KIAS until hdg 283°.
Rwy 13L/R: Do not exceed 270 KIAS until hdg 340°.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 7: Climb heading 074° to 4500, then climbing left turn heading 283°, maintain 5900 or ATC assigned altitude, thence...

TAKEOFF RWY 13 L/R: Climb on heading 131° to 4500, then climbing right turn heading 340°, maintain 5900 or ATC assigned altitude, thence...

TAKEOFF RWY 25: Climb on heading 254° to 4500, then climbing right turn heading 005°, maintain 5900 or ATC assigned altutude, thence...

TAKEOFF RWY 31 L/R: Climb on heading 321°, maintain 5900 or ATC assigned altutude, thence...

...expect radar vectors to first enroute navaid/fix. Expect clearance to requested altitude/flight level five minutes after departure.