

▼

▲

Baro-VNAV NA when using Mount Carmel altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 41°C (105°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Mount Carmel altimeter setting: increase LPV DA to 704 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 855 feet and all visibilities ½ SM; increase all MDAs 40 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat D ¼ SM. Circling to Rwy 36 NA at night.

MISSED APPROACH:
Climb to 2600 direct YONUB and hold.

ASOS 118.0	EVANSVILLE APP CON ★ 125.6 343.7	UNICOM 122.8 (CTAF) 0
---------------	-------------------------------------	--------------------------

ELEV 430		TDZE 428	
4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 26).	
2600 ← 270°		2600 YONUB	
090° →		090° to RWY09	
GP 3.00°		*LNAV only	
TCH 45		NOCNI 1.5 NM to RWY09	
ZUSPU		RWY09	
YUKUB		*940	
2100		5198 X 100	
6.8 NM		5199 X 100	
3.6 NM		36	
1.5 NM		81	
CATEGORY		A	
LPV DA		678-¾ 250 (300-¾)	
LNAV/VNAV DA		829-1¾ 401 (400-1¾)	
LNAV MDA		820-1 392 (400-1)	
CIRCLING		880-1 450 (500-1)	
		900-1 470 (500-1)	
		940-1½ 510 (600-1½)	
		1160-2¼ 730 (800-2¼)	
		REIL Rwy 9, 27, 18 and 36	
		MIRL Rwy 9-27 and 18-36	

LAWRENCEVILLE, ILLINOIS

Amtd 1C 19MAY22

LAWRENCEVILLE-VINCENNES INTL (LWV)

38°46'N-87°36'W

RNAV (GPS) RWY 9