


APP CRS	Rwy Ldg	8926
251°	TDZE	122
	Apt Elev	128

RNAV (RNP) Z RWY 24R
LOS ANGELES INTL (LAX)

RNP AR APCH-GPS.	ALSF-2	MISSED APPROACH: Climb to 2000 on track 251° to IGUPE and track 263° to RAFFS and hold.
▼ Simultaneous approach authorized with HHR. For uncompensated Baro-VNAV systems, procedure NA below 5°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 6000 and RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized.		

D-ATIS	SOCAL APP CON	LOS ANGELES TOWER	GND CON
133.8	124.3 363.2 (APCH from W) 124.9 269.0 (090°-224°) 124.5 235.975 (225°-044°) 128.5 360.7 (045°-089°)	133.9 239.3 (N) 120.95 379.1 (S)	121.65 327.0 (N) 121.75 327.0 (S) 121.4 327.0 (W)



ELEV 128 **D** TDZE 122

TDZ/CL Rwy 6R, 7L, 24R, and 25L
HIRL all Rwy

ROUTING TO BREA (not to scale)

BREA 8000 251° (3.6) → DECOR 9000 251° (3.6) → SKOLL 10000 241° (10.4) → CRCUS 14000 270K 12000 → SEAVU 14000 270K 12000

2000 IGUPE tr 263° RAFFS

See planview for multiple IF locations.

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

KOBEE 2200 MUBME 2500

GP 3.00° TCH 55

6.4 NM 1.2 NM

CATEGORY	A	B	C	D
RNP 0.15 DA		484/40	362 (400-¾)	
RNP 0.30 DA		586/60	464 (500-1½)	

AUTHORIZATION REQUIRED

SW-3, 25 DEC 2025 to 22 JAN 2026

SW-3, 25 DEC 2025 to 22 JAN 2026