

WAAS CH 81807 W36A	APP CRS 356°	Rwy Ldg TDZE 1066 Apt Elev 1087
--	------------------------	---

RNAV (GPS) RWY 36

NEW CENTURY AIRCENTER (IXD)

DME/DME RNP-0.3 NA. For inop MALS, increase LNAV Cat D visibility to 1¼ and LPV visibility to 1 all Cats. If local altimeter setting not received, use Johnson County Exec altimeter setting and increase all DA/MDAs 20 feet. VDP NA with Johnson County Exec altimeter setting.

MALS

MISSED APPROACH: Climb to 3100 direct ZODPU and hold.

ASOS 135.325	KANSAS CITY APP CON 118.9 251.075	NEW CENTURY TOWER ★ 133.0 (CTAF) 0	GND CON 124.3	UNICOM 122.95
------------------------	---	--	-------------------------	-------------------------

The main chart displays the RNAV (GPS) RWY 36 approach. Key features include:

- Initial Approach:** 30 NM to UNOXY, 176° heading, 3100 ft altitude. Turn 086° to UNOXY.
- Intermediate Approach:** 30 NM to NAPVY, 176° heading, 3100 ft altitude. Turn 266° to NAPVY.
- Final Approach:** 30 NM to ANQUM (NoPT), 086° heading, 3100 ft altitude. Turn 266° to ANQUM.
- Altitudes:** 1189 ± A, 2700, 356° (6), 356° (5), 356° (5).
- Distances:** 5 NM, 30 NM, 30 NM, 30 NM.
- Obstacles:** 81, 7339 X 150, 5132 X 100, 36.
- Missed Approach:** 5 NM, 176° heading, 3100 ft altitude. Turn 176° to ZODPU.

ELEV 1087	TDZE 1066
------------------	------------------

The inset chart shows the approach path and altitudes. Key features include:

- Altitudes:** 81, 7339 X 150, 5132 X 100, 36.
- Distances:** 0.5% UP, 0.5% UP.
- Obstacles:** 81, 7339 X 150, 5132 X 100, 36.

5 NM Holding Pattern		ANQUM	JIKLA	3100	ZODPU
3100		176°	356°	356°	*LNAV only.
GP 3.00°		TCH 50	2700	*1.1 NM to RW36	RW36
6 NM		3.9 NM	1.1 NM		
CATEGORY	A	B	C	D	
LPV DA	1316-½ 250 (300-½)				
LNAV/VNAV DA	NA				
LNAV MDA	1440-½ 374 (400-½)			1440-1 374 (400-1)	
CIRCLING	1560-1 473 (500-1)		1580-1½ 493 (500-1½)		1640-2 553 (600-2)

Olathe, Kansas
Amdt 2A 30JAN20

38°50'N-94°53'W

NEW CENTURY AIRCENTER (IXD)

RNAV (GPS) RWY 36

NC-2, 25 DEC 2025 to 22 JAN 2026

NC-2, 25 DEC 2025 to 22 JAN 2026