

ILS or LOC Y RWY 33R

LOC I-RND 109.3	APCH CRS 325°	Rwy Idg TDZE Arprt Elev 8351 733 761	[USAF]
RADAR or DME required			ALSIF-1
* When ALS inop, increase RVR to 40 and vis to 3/4 mile. ** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 1/2 miles. *** Circling not authorized SW of Rwy 15L-33R.			MISSED APPROACH: Climb to 1500, then climbing right turn hdg 084° to 3000. Intercept DHK R-054 to WIMVI and hold.
ATIS ★	SAN ANTONIO APP CON	TOWER ★	GND CON
290.525	128.05 318.1	128.25 294.7	119.65 275.8
CLNC DEL (RWY 15L-33R)		HANGOVER ATIS ★	HANGOVER TOWER ★
338.35		327.8	120.5 291.1
HANGOVER GND CON			
124.75 353.75			

Simultaneous approaches authorized with Rwy 33R and 33L.

EMERG SAFE ALT 100 NM 4100

ELEV	761	TDZE	733
------	------------	------	------------

CATEGORY	A	B	C
S-ILS 33R *	933/24		
S-LOC 33R **	1180/24	447 (500-1/2)	1180/45
	447 (500-7/8)		
*** CIRCLING	1240-1	479 (500-1)	1260-1 1/2
	499 (500-1 1/2)		
	1900-3	1139	(1200-3)