

APP CRS
058°

Rwy Ldg
TDZE
1175

Apt Elev
1175

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

RNAV (RNP) Z RWY 6

RNP AR APCH - GPS.

For uncompensated Baro-VNAV systems,
procedure NA below -14°C or above 54°C.
For inop ALS, increase RNP 0.20 all Cats
visibility to ¾ SM.

MALSR

MISSED APPROACH: (Do not exceed 240K until
DEWET) Climb to 1600 then climbing right turn
to 5000 direct DEWET and hold, continue
climb-in-hold to 5000. *Missed approach requires
minimum climb of 370 feet per NM to 2900.

ATIS 132.375	ROANOKE APP CON 133.225 339.8	ROANOKE TOWER 118.3 257.8	GND CON 121.9 257.8
------------------------	---	-------------------------------------	-------------------------------

MSA RW06 2.5 NM

5700

(IAF) WEXOD

6000 113° (6.5)

6000 072° (5.1)

(IF) DIXXY (RNP 0.3)

3600 068° (7.9)

PKMAN (FAF) YONTE 068° (1.9)

MJAYY 112° (0.6)

BRADB 112° (1.3)

GARCA 058° (2.1)

RW06

MISSED APCH FIX

DEWET 258° 078° 4 NM

ELEV 1175

D

TDZE 1175

GP 3.00° TCH 58

6000 068°

3600

YONTE 3600

PKMAN 3007

MJAYY 2587

BRADB 2396

GARCA 1879

RW06 058°

1600

5000

DEWET

CATEGORY	A	B	C	D
RNP 0.20 DA*		1444-½	269 (300-½)	
RNP 0.30 DA		1605-¾	430 (500-¾)	

AUTHORIZATION REQUIRED

REIL Rwy 6 and 24

HIRL Rwy 6-24 and 16-34

ROANOKE, VIRGINIA

ROANOKE/BLACKSBURG RGNL (WOODRUM FLD) (R.O.A)

37°20'N-79°59'W

RNAV (RNP) Z RWY 6

Orig-A 25JAN24