



WAAS CH 49230 W34A	APP CRS 344°	Rwy Ldg TDZE 4225 Apt Elev 4231
--	------------------------	---

RNAV (GPS) Y RWY 34R
SALT LAKE CITY INTL (SLC)

RNP APCH - GPS. Simultaneous approach authorized. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 49°C. Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV Cat E visibility to RVR 5000, LNAV Cots C/D visibility to RVR 5500, LNAV Cat E visibility to RVR 6000. Cat E restricted to USAF/USN aircraft.	ALSF-2 	MISSED APPROACH: Climb to 9000 direct TCH VORTAC and on track 336° to OGD VORTAC and hold.
---	------------	--

D-ATIS 124.75 125.625	SALT LAKE CITY APP CON 125.7 284.6	SALT LAKE CITY TOWER 119.05 257.8	GND CON 123.775 348.6	CLNC DEL 127.3 379.975	CPDLC
---------------------------------	--	---	---------------------------------	----------------------------------	-------



9000	TCH	ir	336°	OGD	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 73).	PLAGE
9000	tr	336°	OGD	CHEVL	HAKKR	ALGIE
9000	tr	336°	OGD	IRUYU 2 NM to RW34R	6100	11000
9000	tr	336°	OGD	1 NM to RW34R	4900	10000
9000	tr	336°	OGD	RW34R	6100	GP 3.00° TCH 55
9000	tr	336°	OGD	1 NM	1 NM	3.8 NM
9000	tr	336°	OGD	9.1 NM	3.1 NM	2.4 NM
9000	tr	336°	OGD	CATEGORY	A	B
9000	tr	336°	OGD	LPV DA	4425/18	200 (200-½)
9000	tr	336°	OGD	INAV/VNAV DA	4557/26	332 (400-½)
9000	tr	336°	OGD	INAV MDA	4600/24	375 (400-½)
9000	tr	336°	OGD		4600/35	375 (400-¾)
9000	tr	336°	OGD			4640/40
9000	tr	336°	OGD			415 (500-¾)