



LOC I-SBN	APP CRS	Rwy Ldg
109.3	274°	8412
		TDZE
		774
		Apt Elev
		798

ILS or LOC RWY 27L
SOUTH BEND INTL (SBN)

RNP APCH - GPS. From NORNA.	MALSR	MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct MISHA LOM/RADAR and hold, continue climb-in-hold to 3000.
ADF required.		
▼ Circling Rwy 27R NA at night.		
▲ * RVR 1800 authorized with use of FD or AP or HUD to DA.		

ATIS 120.675	SOUTH BEND APP CON★ 118.55 257.8	SOUTH BEND TOWER★ 135.675 (CTAF) 0 257.8	GND CON 121.7
------------------------	--	--	-------------------------



1500	3000	SB	SB LOM MISHA RADAR	Remain within 10 NM
6000	1961	094°	2400	GS 3.00° TCH 53
2000	274°			
3.6 NM				
CATEGORY	A	B	C	D
S-ILS 27L *	974/24 200 (200-½)			
S-LOC 27L	1220/24 446 (500-½)		1220/45 446 (500-¾)	
CIRCLING	1280-1 482 (500-1)		1440-1¾ 642 (700-1¾) 1520-2¼ 722 (800-2¼)	