

WAAS CH 65638 W23A	APP CRS 235°	Rwy Ldg TDZE 78 Apt Elev 79	5000
--	------------------------	---	-------------

RNAV (GPS) RWY 23

NEW BEDFORD RGNL (E W B)

RNP APCH-GPS.

▼


Baro-VNAV and VDP NA when using Taunton altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Taunton altimeter setting and increase LPV DA to 393 feet, increase LNAV/VNAV DA to 412 feet; increase all MDA 40 feet and LNAV Cats C and D and Circling Cat C visibility ¼ SM. For inop MALSR, increase LPV all Cats visibility ½ mile, LNAV/VNAV and LNAV Cat A/B visibility ¼ mile. For inop MALSR, when using Taunton altimeter setting, increase LNAV/VNAV all Cats visibility ¾ mile, LNAV Cat A/B visibility ¼ mile and Cat C/D visibility ¾ mile.

MALSR

MISSED APPROACH:

Climb to 2100 direct BONNI and hold.

ATIS 126.85	PROVIDENCE APP CON* 128.7 269.525	NEW BEDFORD TOWER* 118.1 (CTAF) 239.0	GND CON 121.9	UNICOM 122.95
-----------------------	---	---	-------------------------	-------------------------



ELEV 79

TDZE 78

MIRL Rwy 14-32

HIRL Rwy 5-23

REIL Rwy 32

2100		BONNI	KANJI 2.7 NM to RW23		ZEDVI 1700	FURBS	2500
*LNAV only.		*1.2 NM to RW23					
RW23		980*	1700		GP 3.00° TCH 46		
1.2		1.5 NM	2.3 NM	6.1 NM			
CATEGORY	A		B	C	D		
LPV DA	359-¾		281 (300-¾)				
LNAV/VNAV DA	378-¾		300 (300-¾)				
LNAV MDA	500-¾		422 (500-¾)				
CIRCLING	620-1		640-1		720-1¾		960-3
	541 (600-1)		561 (600-1)		641 (700-1¾)		881 (900-3)