



LOC/DME I-RDD	APP CRS	Rwy Ldg	6997
108.7	346°	TDZE	499
Chan 24		Apf Elev	505

ILS or LOC RWY 34

REDDING RGNL (RDD)

DME required for LOC only.			MALSR 	MISSED APPROACH: Climb to 1700 then climbing right turn to 5000 on heading 090° and RDD R-044 to ITMOR INT/RDD 12 DME and hold, continue climb-in-hold to 5000.
For inop ALS, increase S-ILS 34 Cat E visibility to ¾ SM and S-LOC 34 Cat C/D/E visibility to 1 SM.				
ATIS 124.1	OAKLAND CENTER 132.2 350.3	REDDING TOWER ★ 119.8(CTAF) 0 269.25	GND CON 121.7	UNICOM 122.95



1700 5000 RDD R-044 ITMOR LASSN I-RDD 8.1 VGSI and ILS glidepath not coincident (VGSi Angle 3.00/TCH 55).	Use I-RDD DME when on the localizer course. * LOC only.	CUYAP I-RDD 3.6 I-RDD 1.3	2700 1260*	166° DIBLE I-RDD 18 3000 3000 GS 3.00° TCH 52	2.3 NM 4.5 NM 9.9 NM
CATEGORY	A	B	C	D	E
S-ILS 34	699-½ 200 (200-½)				
S-LOC 34	840-½	341 (400-½)	840-⅝	341 (400-⅝)	
CIRCLING	940-1 435 (500-1)	1000-1 495 (500-1)	1120-1¾ 615 (700-1¾)	1340-2¾ 835 (900-2¾)	1340-3 835 (900-3)