

ILS or LOC/DME RWY 27

LOC I-VOK **APCH CRS** **Rwy Idg THRE** **Arprt Elev**

108.5	269°	9000 904 912
--------------	-------------	---

AL-714 [USAF] **VOLK FLD (KVOK)**

*** When ALS inop, increase vis to ¾ mile.**
**** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.**

ALSF-1

MISSED APPROACH: Climb to 2200, then climbing left turn to 4000 via DLL VORTAC R-304 direct DLL and hold.

ATIS	APP CON	TOWER *	GND CON
134.35 257.85	135.25 244.875	127.5 0 (CTAF) 239.25 0	121.9 275.8

*** Circling NA South of Rwy 9-27.

LOCALIZER 108.5 I-VOK

VOLK Chan 41 VOK

YELOH VOK 6

ADAMZ VOK 12

IBUCK VOK 15

DLLS 117.0 DLL Chan 117

EMERG SAFE ALT 100 NM 4200

ELEV	THRE
912	904

S-ILS 27 * **1104/24** **200 (200-½)**

S-LOC 27 ** **1320/24 416 (500-½)** **1320/40 416 (500-¾)**

CIRCLING ***

Category	A	B	C	D	E
S-ILS 27 *	1400-1 488 (500-1)	1500-1 588 (600-1)	1500-1½ 588 (600-1½)	1500-2 588 (600-2)	1580-2¼ 668 (700-2¼)

HIRL Rwy 9-27 0

Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30