

WAAS CH 45807 W08B	APP CRS 078°	Rwy Ldg 11200 TDZE 944 Apt Elev 944
--	------------------------	--

RNAV (GPS) Y RWY 8L

ONTARIO INTL (ONT)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). Circling NA north of Rwy 8L-26R.
DME/DME RNP -0.3 NA. For inoperative MALSR increase LPV visibility all Cats to RVR 6000.

MALSR

A5

MISSED APPROACH:

Climb to 4400 direct CABUB and on track 168° to PDZ VORTAC and hold, continue climb-in-hold to 4700.

D-ATIS 124.25	SOCAL APP CON 127.0 318.2	ONTARIO TOWER 120.6 360.775	GND CON 121.9 257.8	CLNC DEL 132.9	CPDLC
-------------------------	-------------------------------------	---------------------------------------	-------------------------------	--------------------------	-------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/ TCH 62).

5 NM Holding Pattern

4700 ← 258°
078° →

GP 3.00°
TCH 45

PECIN

APIPE

2800

2800

6 NM

4.1 NM

1.5

RWY 8L

*LNAV only.

*1.5 NM to RWY 8L

4400

CABUB

168° tr

PDZ

CATEGORY	A	B	C	D
LPV DA	1266/30 322 (400-5%)			
LNAV/VNAV DA	1520-1½ 576 (600-1½)			
LNAV MDA	1480/24 536 (600-½)		1480/55 536 (600-1)	
CIRCLING	1480-1 536 (600-1)		1540-1½ 596 (600-1½) 1600-2 656 (700-2)	

078°

1219Z X 150

10200 X 150

TWR

26R

26L

ONTARIO, CALIFORNIA
Amdt 1D 26MAY16

34°03'N-117°36'W

ONTARIO INTL (ONT)

RNAV (GPS) Y RWY 8L