

WAAS

CH **60909**

**W29A**

APP CRS

**291°**

Rwy Ldg

**6525**

TDZE

**871**

Apt Elev

**871**

**RNAV (GPS) RWY 29**

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using General Downing-Peoria Intl altimeter setting. When local altimeter setting not received, use General Downing-Peoria Intl altimeter setting: increase all DA 116 feet and all MDA 120 feet; increase LPV all Cats visibility to RVR 3500, LNAV/VNAV all Cats and LNAV Cats C/D visibility ¾ mile, and Circling Cats C/D visibility ¼ mile. For inoperative MALSRs when using General Downing-Peoria Intl Regional altimeter setting increase LPV all Cats visibility ½ mile, and LNAV Cat C/D visibility ¾ mile.

MALSR

MISSED APPROACH:  
Climb to 2500 direct  
ZEXED and hold.

|                        |                                             |                                                    |                          |                         |
|------------------------|---------------------------------------------|----------------------------------------------------|--------------------------|-------------------------|
| ATIS<br><b>119.575</b> | SAINT LOUIS APP CON<br><b>128.725 256.9</b> | BLOOMINGTON TOWER ★<br><b>124.6 (CTAF) 269.575</b> | GND CON<br><b>121.65</b> | UNICOM<br><b>122.95</b> |
|------------------------|---------------------------------------------|----------------------------------------------------|--------------------------|-------------------------|

