

VORTAC EUF	APP CRS	Rwy Ldg
109.2	356°	5000
Chan 29		TDZE 285
		Apt Elev 285



VOR/DME RWY 36
WEEDON FLD (EUF)

▼ When local altimeter setting not received, use Columbus, GA altimeter setting and increase all MDAs 40 feet and S-36 visibility Cats C and D ½ SM and Circling Cats C and D ¼ SM. Rwy 36 helicopter visibility reduction below ¾ SM NA.

▲ NA

MISSED APPROACH: Climb to 1500 then climbing right turn to 2000 direct EUF VORTAC and hold.

ASOS 128.325	ATLANTA APP CON ★ 125.5 323.1	CINC DEL 134.25 339.8	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------	---------------------------------



1500	2000	EUF	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 25). EUF VORTAC	Remain within 10 NM
CATEGORY	A	B	C	D
S-36	780-1	495 (500-1)	780-1 ¾	495 (500-1 ¾)
CIRCLING	920-1	635 (700-1)	1060-2 ¼ 775 (800-2 ¼)	1060-2 ½ 775 (800-2 ½)

SE-4, 25 DEC 2025 to 22 JAN 2026

SE-4, 25 DEC 2025 to 22 JAN 2026