

WAAS CH 82509 W21A	APP CRS 211°	Rwy Idg 4200 TDZE 823 Apt Elev 823
--	------------------------	---

RNAV (GPS) RWY 21

RNP APCH - GPS



T Rwy 21 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Baro-VNAV and VDP NA
A when using Indianapolis Intl altimeter setting. For uncompensated Baro-VNAV
 systems, LNAV/VNAV NA below 0°C or above 54°C. Inop table does not apply.
 When local altimeter setting not received, use Indianapolis Intl altimeter setting
 and increase all MDA's 20 feet.

MALS



MISSED APPROACH:
Climbing right turn to 2900
direct ANTI and hold.

ASOS 121.575	INDIANAPOLIS APP CON 119.05 317.8	CLINC DEL 128.6	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------	---------------------------------



CATEGORY		A	B	C	D
LPV	DA	1091-1	268 (300-1)		NA
RNAV/ VNAV	DA	1076-1	253 (300-1)		NA
RNAV	MDA	1200-1	377 (400-1)		NA
 CIRCLING		1320-1	497 (500-1)	1500-2 677 (700-2)	NA

