

WAAS CH 66008 W18A	APP CRS 181°	Rwy Idg 5002 TDZE 239 Apt Elev 239
--	------------------------	---


RNAV (GPS) RWY 18
NEWPORT RGNL (M19)

RNP APCH-GPS.

- ⚠** When local altimeter setting not received, use **Batesville altimeter setting**: increase LPV DA to 575 feet and all **visibilities ½ SM**; increase LNAV/VNAV DA to 845 feet and all **visibilities ½ SM**; increase all MDAs 100 feet and **visibility Cts C ½ SM and D ½ SM**. VDP NA when using Batesville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV NA when using Batesville altimeter setting.

MISSED APPROACH: Climb to 3000 direct VURHU and hold.

AWOS-3PT 118.15	MEMPHIS CENTER 120.075 289.4	UNICOM 122.8 (CTAF) 0
---------------------------	--	--



CATEGORY	A	B	C	D
LPV DA	489- ³ / ₄	250 (300- ³ / ₄)		
LNNAV/ VNAV DA	759-1 ³ / ₄	520 (600-1 ³ / ₄)		
LNNAV MDA	700-1	461 (500-1)	700-1 ¹ / ₂ 461 (500-1 ¹ / ₂)	700-1 ¹ / ₂ 461 (500-1 ¹ / ₂)
CIRCLING	760-1	521 (600-1)	760-1 ¹ / ₂ 521 (600-1 ¹ / ₂)	900-2 661 (700-2)

