

WAAS
CH **99600**
W36A

APP CRS
002°

Rwy Idg **8003**
TDZE **261**
Apt Elev **264**

RNAV (GPS) RWY 36

GOLDEN TRIANGLE RGNL (GTR)

RNP APCH.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Columbus AFB altimeter setting: increase LPV DA to 500 feet, LNAV/VNAV DA to 593 feet and LNAV/VNAV visibility ½ SM; increase all MDAs 40 feet. Baro-VNAV and VDP NA when using Columbus AFB altimeter setting.

MISSED APPROACH:
Climb to 3000 direct HUYKA and hold.

ATIS 126.375	COLUMBUS APP CON ★ 135.6 323.275	GOLDEN TRIANGLE TOWER ★ 118.2 (CTAF) 0 298.875	GND CON 135.375 322.475	CLNC DEL 135.375 322.475
------------------------	--	--	-----------------------------------	------------------------------------

MISSED APCH FIX

7 NM

182°

HUYKA

593

Λ

Λ 449

RW36

372±

Λ

JAKVU

2.7 NM to RW36

(FAF)

BAWMO

Λ 854

Λ 1005

2000

002°

(6.3)

(IF/IAF)

DIXVU

002°

182°

7 NM

HOLD

6000

3000

30 NM to DIXVU

3000

DIXVU

092°

272°

30 NM to DIXVU (NoPT)

3000

DIXVU

092°

272°

CLNC DEL

126.25

(when twr closed)

UNICOM

122.95

A-440

A-440

ELEV 264

TDZE 261

7 NM Holding Pattern

DIXVU

BAWMO

JAKVU

2.7 NM to RW36

*1 NM to RW36

RW36

GP 3.00°

TCH 42

6000

3000

182°

002°

002°

2000

*1140

6.3 NM

2.7 NM

1.7 NM

1 NM

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 55).

3000

HUYKA

*LNAV only.

CATEGORY	A	B	C	D	E
LPV DA	461-3¼ 200 (200-¾)				
LNAV/VNAV DA	554-7⁄8 293 (300-7⁄8)				
LNAV MDA	640-1 379 (400-1)		640-1⅛ 379 (400-1⅛)		
CIRCLING	760-1 496 (500-1)		960-2 696 (700-2)	960-2¼ 696 (700-2¼)	960-2½ 696 (700-2½)

81

45

8003 X 150

36

002° to RW36

HIRL Rwy 18-36 0