

(DALL4.TTT) 25331
DALLAS FOUR DEPARTURE

AL-5936 (FAA)

LANCASTER RGNL (LNC)
LANCASTER, TEXASLONE STAR DEP CON
125.2 343.65


RADAR and DME required.

NOTE: BELCHER Transition: For aircraft inbound to
the JAN, MLU, and SHV terminal areas only.
NOTE: SOLD0 Transition: ATC assigned.**TOP ALTITUDE:
ASSIGNED BY ATC**BONHAM
114.6 BYP 
Chan 93MAVERICK
113.1 TTT 
Chan 78COBUG
5000
*2300
064°
(38)NOBLY
5000
*2100
064°
(38)TRISS
7500
*2100
074°
(39)SOLD0
3000
*2300
084°
(36)CLARE
5000
*2400
094°
(36)9000
*2100
094°
(34)GREGG COUNTY
112.9 GGG 
Chan 76

ORTRO

TEXARKANA
116.3 TXK 
Chan 110**TAKEOFF MINIMUMS**

Rwy 13: Standard.

Rwy 31: 300-1¼ or standard with a minimum climb
of 210'/NM to 800, or alternatively, with
standard takeoff minimums and a normal
200'/NM climb gradient, takeoff must occur
no later than 1300' prior to DER.BELCHER
117.4 EIC 
Chan 121

TEKBE

SHRLY

POTEN

R-346

R-346

R-346

R-346

R-346

R-346

R-346

(*CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

DALLAS FOUR DEPARTURE
(DALL4.TTT) 27NOV25LANCASTER, TEXAS
LANCASTER RGNL (LNC)

▼	DEPARTURE ROUTE DESCRIPTION
	<u>TAKEOFF RUNWAY 31</u>: Climb on heading 314° to 1800 before turning left.
	Fly assigned heading for RADAR vectors to appropriate route. Maintain ATC assigned altitude.
	<u>BELCHER TRANSITION (DALL4.EIC)</u>: From over TTT VOR/DME on TTT R-094 to POTEN, then on EIC R-259 to EIC VORTAC.
	<u>LITTLE ROCK TRANSITION (DALL4.LIT)</u>: From over TTT VOR/DME on TTT R-064 to ORTRO, then on LIT R-237 to LIT VORTAC.
	<u>SOLDO TRANSITION (DALL4.SOLDO)</u>: From over TTT VOR/DME on TTT R-084 to SOLDO.
	<u>TEXARKANA TRANSITION (DALL4.TXK)</u>: From over TTT VOR/DME on TTT R-074 to SHERO, then on TXK R-244 to TXK VORTAC.

SC-2, 25 DEC 2025 to 22 JAN 2026

SC-2, 25 DEC 2025 to 22 JAN 2026