

WAAS CH 58321 W33A	APP CRS 330°	Rwy Ldg TDZE Apt Elev	5000 1713 1718
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 33

MADISON MUNI (MDS)

RNP APCH - GPS.

▼


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 33°C. Rwy 33


▲

helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Brookings altimeter setting: increase LPV DA to 2021 feet; increase LNAV/VNAV DA to 2071 feet and all visibilities ¼ SM; increase all MDAs 60 feet and visibility LNAV and Circling Cats C and D ¼ SM. Circling NA to Rwy's 3 and 21. Baro-VNAV NA when using Brookings altimeter setting.

MISSED APPROACH:
Climb to 3400 direct
YISRU and hold.

AWOS-3 118.35	MINNEAPOLIS CENTER 132.05 317.4	GCO 121.725	UNICOM 122.8 (CTAF) 
-------------------------	---	-----------------------	---



	YISRU		YUED		GIZBU	
	3400		3400		3400	
	1.2 NM to RWY 33		330°		150°	
	RWY 33		3400		330°	
	1.2		4 NM		6.1 NM	
CATEGORY	A		B		C	
LPV DA	1963-1		250 (300-1)			
LNAV/VNAV DA	2013-1		300 (300-1)			
LNAV MDA	2120-1		407 (500-1)		2120-1½ 407 (500-1½)	
CIRCLING	2180-1		462 (500-1)		2400-2 682 (700-2)	
					2400-2¼ 682 (700-2¼)	