

APP CRS
293°

Rwy Idg
2801

TDZE
833

Apt Elev
833

▼

▲

Circling to Rwy 23 NA at night. Rwy 29 helicopter visibility reduction below 1 SM NA. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Dodge County altimeter setting and increase all MDAs 60 feet and LNAV visibility Cat C/D ½ SM.

RNAV (GPS) RWY 29

WATERTOWN MUNI (RYV)

AWOS-3
119.975

MADISON APP CON ★
119.15 343.7

UNICOM
122.8 (CTAF)

MISSED APPROACH: Climb to 3000 direct JUTGI and right turn via 329° track to UCILU and hold.

The main chart displays the RNAV (GPS) RWY 29 approach. Key features include:

- Waypoints:** UCILU (4 NM, 158°/338°), JUTGI (1220', 329°/8.6°), RW29 (1158', 1020±), ATOHU (1039±), GOROJ (2500', 293°/7°), DOHJU (3000', 023°/5°), VUCBU (3000', 203°/5°), and BADGER BAE (3000', 261°/8°).
- Obstacles:** EWAWI (1361'), A 1630, and GREAS (3000', 021°/4.9°).
- MSA:** Minimum Safe Altitude for RWY 29 is 25 NM with a 2700' ceiling.
- Altitudes:** Various altitudes are marked along the path, including 1220', 1360', 1020±, 1158', 1039±, 2500', 3000', and 2700'.
- Distances:** Distances between waypoints are provided in NM and degrees.

ELEV 833

D

TDZE 833

2801 X 75

0.43° UP

4429 X 75

293°

11

2

3000

JUTGI

tr 329°

UCILU

RW29

ATOHU

GOROJ

3000

293°

2500

3.04°

TCH 40

5 NM

7 NM

CATEGORY	A	B	C	D
LNAV MDA	1400-1 567 (600-1)	1400-1½ 567 (600-1½)	1400-1¾ 567 (600-1¾)	1400-2 567 (600-2)
CIRCLING	1400-1 567 (600-1)	1440-1 607 (700-1)	1720-2¾ 887 (900-2¾)	1720-3 887 (900-3)

REIL Rwy 5 and 23

MIRL Rwy 5-23 and 11-29

WATERTOWN, WISCONSIN

Orig-B 04NOV21

43°10'N-88°43'W

WATERTOWN MUNI (RYV)

RNAV (GPS) RWY 29