

WAAS CH 81836 W05A	APP CRS 054°	Rwy Idg TDZE 255 Apt Elev 270
--	------------------------	---

RNAV (GPS) RWY 5

COLUMBIA/MARION COUNTY (ØRØ)

RNP APCH - GPS.


▼

NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.
When local altimeter setting not received, use Hattiesburgh/Laurel Rgnl altimeter setting and increase all DA 66 feet and all MDA 80 feet; increase LPV all Cats visibility ½ mile and LNAV/VNAV all Cats and Circling Cat C visibilities ¼ mile, increase Circling Cat D visibility ½ mile, increase LNAV Cat C and D visibility ¾ mile. VDP and Baro-VNAV NA when using Hattiesburgh/Laurel Rgnl altimeter setting. Rwy 5 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2400 direct
NERAE and hold.

AWOS-3PT 120.675	HOUSTON CENTER 126.8 327.8	UNICOM 122.8 (CTAF)Ø
----------------------------	--------------------------------------	--------------------------------



4 NM Holding Pattern		HULNA	ZOSOG	CECAK 2 NM to RW05	2400	NERAE
2400		234°	054°	054°	1500	*1.5 NM to RW05
GP 3.00°		TCH 40	1500	*920	RW05	
6.1 NM		1.8 NM	0.5 NM	1.5 NM	*NAV only.	
CATEGORY	A	B	C	D		
LPV DA	505-7½		250 (300-7½)			
LNAV/VNAV DA	743-1½		488 (500-1½)			
LNAV MDA	760-1	505 (500-1)	760-1¾	505 (500-1¾)		
CIRCLING	760-1 490 (500-1)	820-1 550 (600-1)	920-1¾ 650 (700-1¾)	1000-2¼ 730 (800-2¼)	REIL Rwy 5 and 23Ø	
					MIRL Rwy 5-23 Ø	