

WAAS CH 58308 W18A	APP CRS 176°	Rwy ldg 5200 TDZE 826 Apt Elev 831
--	------------------------	---

RNAV (GPS) RWY 18


GROVE RGNL (G.M.J)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 3000 direct OJEFY and hold.

AWOS-3PT 119.025	KANSAS CITY CENTER 128.6 282.325	UNICOM 122.8 (CTAF)
----------------------------	--	-------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 2.75\TCH 31).				
4 NM Holding Pattern		UNHAF	VEGJU	RICOY 3 NM to RW18
3000 ← 356°		176° →	176°	*LNAV only.
GP 3.00° TCH 40		2600	*1820	RW18
		6.1 NM	2.4 NM	3 NM
CATEGORY	A	B	C	D
LPV DA	1153-1¼		327 (400-1¼)	NA
LNAV/VNAV DA	1346-2		520 (600-2)	NA
LNAV MDA	1240-1	414 (500-1)	1240-1¼ 414 (500-1¼)	NA
CIRCLING	1500-1	669 (700-1)	1500-1¼ 669 (700-1¼)	NA

