

WAAS CH 86625 W20A	APP CRS 198°	Rwy Ldg TDZE Apt Elev	6001 501 501
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20

JOHN C TUNE (JWN)


⚠

⚠ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Nashville Intl altimeter setting and increase all DA 40 feet and all visibilities ½ mile; increase all MDA 40 feet and LNAV Cats C and D visibility ½ mile. Circling NA east of Rwy 2-20. Baro-VNAV and VDP NA when using Nashville Intl altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 1200 then
climbing right turn to
3000 direct BEVEE
and hold.

ATIS 127.075	NASHVILLE APP CON 119.35 372.0	JOHN TUNE TOWER ★ 119.45 (CTAF)	GND CON 121.7	UNICOM 122.7
------------------------	--	---	-------------------------	------------------------



198°

4001 x 100

TWIR

0.7% UP

1200

3000

BEVEE

*LNAV only.

JOGIS 3.2 NM to RW20

*1.8 NM to RW20

RW20

*1560

2500

2500

198°

018°

2700

4 NM Holding Pattern

BICOL

TWITY

2500

1.8 NM

1.4 NM

3 NM

4.8 NM

GP 3.00°

TCH 40

CATEGORY	A		B		C		D	
LPV DA	856-1¼		355 (400-1¼)					
LNAV/VNAV DA	1003-1¾		502 (600-1¾)					
LNAV MDA	1120-1	619 (700-1)			1120-1¾	619 (700-1¾)		
CIRCLING	1200-1	699 (700-1)			1340-2½	839 (900-2½)	1340-2¾	839 (900-2¾)

MIRL Rwy 2-20

REIL Rwy 2 and 20