

WAAS  
CH **40428**  
**W25A**

APP CRS  
**263°**

Rwy Ldg **12000**  
TDZE **5355**  
Apt Elev **5434**

RNAV (GPS) Y RWY 25

DENVER INTL (DEN)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 46°C (116°F). Simultaneous approach authorized with Rwy 26.  
DME/DME RNP-0.3 NA. Use of FD or AP providing track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations.  
For inoperative MALSR, increase LNAV/VNAV all Cats visibility to RVR 4500.  
#RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 10000 direct GIVTE and on track 315° to HYGEN and hold.

|                              |                                                                     |                                      |                                                                 |
|------------------------------|---------------------------------------------------------------------|--------------------------------------|-----------------------------------------------------------------|
| D-ATIS<br><b>125.6 379.9</b> | DENVER APP CON<br><b>119.3 307.3 (N)</b><br><b>120.35 379.3 (S)</b> | DENVER TOWER<br><b>128.75 273.55</b> | GND CON<br><b>121.35 379.175 (W)</b><br><b>121.85 377.1 (E)</b> |
|------------------------------|---------------------------------------------------------------------|--------------------------------------|-----------------------------------------------------------------|

MISSED APCH FIX

RADAR REQUIRED

ELEV 5434

**D**

TDZE 5355

HIRL all Rwys  
TDZ/CL Rwys 7, 16L, 16R, 17R,  
26, 34L, 34R, 35L, 35R

10000

GIVTE

tr 315°

HYGEN

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 83).

ETHAL

10000

\*LNAV only

GP 3.00°

TCH 55

| CATEGORY     | A                   | B | C                   | D |
|--------------|---------------------|---|---------------------|---|
| LPV DA#      | 5555/24 200 (200-½) |   |                     |   |
| LNAV/VNAV DA | 5700/30 345 (300-⅝) |   |                     |   |
| LNAV MDA     | 5800/24 445 (400-½) |   | 5800/45 445 (400-¾) |   |

DENVER, COLORADO

DENVER INTL (DEN)

Amtd 1B 07DEC17

39°52'N-104°40'W

RNAV (GPS) Y RWY 25