

WAAS CH 93518 W16A	APP CRS 164°	Rwy Idg TDZE 2433 Apt Elev 2437
--	------------------------	---


RNAV (GPS) RWY 16

MADRAS MUNI (S33)

Baro-VNAV NA when using Redmond altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). Rwy 16 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Redmond altimeter setting and increase all DA and MDA 580 feet; increase LPV all Cats visibility 2 ½ SM, LNAV/VNAV all Cats visibility 2 ½ SM, LNAV and Circling Cat A visibility ¼ SM, LNAV and Circling Cat B visibility ½ SM, and increase LNAV and Circling Cat C visibility ¼ SM.

MISSED APPROACH: Climb to 7000 direct HUKRI and on track 074° to JOREM and on track 042° to ZEMAB and hold.

AWOS-3PT 132.425	SEATTLE CENTER 126.15 269.475	UNICOM 122.8 (CTAF)
----------------------------	---	-------------------------------



HUKRI		074° (8.8)		JOREM	
HETIM		7000 ↑	HUKRI ✧	JOREM tr 074° ✧	ZEMAB tr 042° △
5500		164°		* LNAV only	
TIWEP		4600		RW16	
4000		KIKCE 4000		FEPOS 3.2 NM to RW16	
GP 3.00° TCH 54		* 3500			
3.8 NM		2.4 NM		1.6 NM	
A		B		C	
CATEGORY	A		B		D
LPV DA	2783-1½		350 (400-1½)		NA
LNAV/ VNAV DA	2843-1¾		410 (500-1¾)		NA
LNAV MDA	3040-1	607 (700-1)	3040-1¾ 607 (700-1¾)		NA
CIRCLING	3040-1	603 (700-1)	3040-1¾ 603 (700-1¾)		NA

