


WAAS CH 99311 W12A	APP CRS 123°	Rwy Idg 4000 TDZE 42 Apt Elev 42
--	------------------------	---

RNAV (GPS) RWY 12
QUINHAGAK (AQH) (PAQH)

RNP APCH.	Procedure NA at night. Baro-VNAV and VDP NA when using Kipnuk altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. When local altimeter setting not received, use Kipnuk altimeter setting and increase all DA and MDA 160 feet; increase LPV all Cats visibility and LNAV/VNAV all Cats visibility 1/8 SM, LNAV Cats C, D visibility 3/8 SM, increase Circling Cat C visibility 1/2 SM, increase Circling Cat D visibility 1/4 SM.	MISSED APPROACH: Climb to 5200 direct CUTEB and hold, continue climb-in-hold to 5200.
-----------	---	---

AWOS-3P 121.575	ANCHORAGE CENTER 125.2 372.0	KENAI RADIO 122.1	UNICOM 122.8 (CTAF) 0
---------------------------	--	-----------------------------	---------------------------------



4 NM Holding Pattern		HOTKU		JOSAD		RWY12	
6000		2500		1600		1600	
GP 3.00°		TCH 35		5.9 NM		3.4 NM	
123°		303°		123°		123°	
CUTEB		5200		1.4 NM to RWY12		RWY12	
*LNAV only.		5.9 NM		3.4 NM		1.4 NM	
CATEGORY		A	B	C	D		
LPV DA		292-1		250 (300-1)			
LNAV/VNAV DA		292-1		250 (300-1)			
LNAV MDA		500-1		458 (500-1)		500-1 3/8 458 (500-1 3/8)	
CIRCLING		500-1		458 (500-1)		580-1 1/2 538 (600-1 1/2) 600-2 558 (600-2)	

ELEV 42	TDZE 42
MIRL Rwy 12-30 0	