

WAAS CH 63017 W16A	APP CRS 162°	Rwy Ldg 10000 TDZE 69 Apt Elev 69
--	------------------------	--

RNAV (GPS) RWY 16

NORTHWEST FLORIDA BEACHES INTL (ECP)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Destin altimeter setting and increase all DA 88 feet, increase all MDA 100 feet, and increase LNAV/VNAV all Cats visibility and LNAV Cat C and D visibility 3⁄8 mile. Baro-VNAV and VDP NA when using Destin altimeter setting. For inop MALSR, increase LNAV Cat C and D visibility to 1 mile. For inop MALSR when using Destin altimeter setting, increase all LPV visibility to 7⁄8 mile, increase all LNAV/VNAV visibility to 1 3⁄8 mile, and increase LNAV Cat C and D visibility to 1 3⁄8 mile.

MALSR

MISSED APPROACH: Climb to 500 then climbing left turn to 4000 direct SCARE and hold, continue climb-in-hold to 4000.

ATIS 119.975	TYNDALL APP CON★ 125.2	PANAMA CITY TOWER★ 118.95 (CTAF) 0	GND CON 121.65
------------------------	----------------------------------	--	--------------------------

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

500

4000

SCARE

3000

GP 3.00° TCH 55

342°

162°

162°

2000

2000

660

1.7 NM to RW16

1 NM to RW16

RW16

SCARE

*LNAV only.

6 NM

4.2 NM

0.7 NM

1 NM

CATEGORY	A	B	C	D
LPV DA		269-1⁄2	200 (200-1⁄2)	
LNAV/VNAV DA		478-7⁄8	409 (500-7⁄8)	
LNAV MDA	440-1⁄2	371 (400-1⁄2)	440-5⁄8	371 (400-5⁄8)
CIRCLING	520-1	451 (500-1)	520-1 1⁄2	620-2
			451 (500-1 1⁄2)	551 (600-2)

TDZ/CL Rwy 16 0

HIRL Rwy 16-34 0

REIL Rwy 34 0

PANAMA CITY, FLORIDA
Amdt 2A 29MAY14

30°22'N-85°48'W

NORTHWEST FLORIDA BEACHES INTL (ECP)
RNAV (GPS) RWY 16