

WAAS CH 93742 W35A	APP CRS 353°	Rwy Ldg TDZE Apt Elev	5500 1409 1409
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35

SIoux COUNTY RGnL (SXX)

RNP APCH - GPS.

Baro-VNAV and VDP NA when using LRJ altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use LRJ altimeter setting: increase LPV DA to 1668 feet; increase LNAV/VNAV DA to 1718 feet; increase all MDAs 60 feet and LNAV visibility Cat C/D ½ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM, and LNAV Cat C/D visibility to ¾ SM. For inop ALS when using LRJ altimeter setting, increase LNAV/VNAV all Cats visibility to ¾ SM, and LNAV Cat C/D visibility to 1 SM.

MALSR

45

MISSED APPROACH: Climb to 4500 direct HALGA and hold, continue climb-in-hold to 4500.

AWOS-3P 120.075	SIoux CITY APP CON ★ 124.6 307.0	UNICOM 122.7 (CTAF)
---------------------------	--	-------------------------------

MISSED APCH FIX

5 NM

172°

352°

HALGA

30 NM to SKYLE

4500

082°

262°

SKYLE

082°

262°

SKYLE

4500

30 NM to SKYLE (NoPT)

RW35

A1461±

SNARK

2 NM to RW35

(FAF)

SIPEE

3300

353°

(7)

(IF/IAF)

SKYLE

353°

173°

5 NM

HOLD

8000

4500

4500

HALGA

SNARK

2 NM to RW35

SIPEE

3300

SKYLE

5 NM Holding Pattern

173°

8000

353°

4500

GP 3.00°

TCH 40

RW35

0.9 NM to RW35

2100

353°

3300

0.9 NM

1.2 NM

3.8 NM

7 NM

CATEGORY	A	B	C	D
LPV DA		1609-½	200 (200-½)	
LNAV/VNAV DA		1659-½	250 (300-½)	
LNAV MDA		1720-½	311 (400-½)	
CIRCLING	1820-1 411 (500-1)	2080-1 671 (700-1)	2080-2 671 (700-2)	2080-2¼ 671 (700-2¼)

ELEV 1409

TDZE 1409

L1

4

5500 X 100

35

353°

REIL Rwy 17

MRL Rwy 17-35

MAURICE, IOWA

Orig-A 02OCT25

42°59'N-96°10'W

SIoux COUNTY RGnL (SXX)

RNAV (GPS) RWY 35