


WAAS CH 50447 W22A	APP CRS 214°	Rwy Ldg TDZE Apt Elev	13502 3606 3607
--	------------------------	-----------------------------	--

RNAV (GPS) Y RWY 22
RICK HUSBAND AMARILLO INTL (AMA)

RNP APCH - GPS.			MALSR 	MISSED APPROACH: Climb to 4020 then climbing left turn to 5000 direct CAUDE and hold.	
For inop ALS, increase LP Cats A/B visibility to 1 SM and Cats C/D/E to ½ SM. Increase LNAV Cats A/B visibility to 1 SM and Cats C/D/E to 1½ SM.					
ATIS 118.85 350.3	AMARILLO APP CON★ 119.5 307.0	AMARILLO TOWER★ 118.3(CTAF) 0 257.9	GND CON 121.9 348.6	CLNC DEL 121.65 239.275	UNICOM 122.95



VGSI and descent angles not coincident
(VGSI Angle 3.00/TCH 77). ELTIC Holding Pattern

CATEGORY	A	B	C	D	E
LP MDA	3900-¾ 294 (300-¾)				
LNAV MDA	4020-¾ 414 (500-¾)				
CIRCLING	4080-1	473 (500-1)	4240-¾ 633 (700-¾)	4280-2¼ 673 (700-2¼)	4460-3 853 (900-3)

REIL Rwy 13
HIRL Rws 4-22 and 13-31

REIL Rwy 13 0
HIRL Rwy 4-22 and 13-31 0