

TACAN SKE	APP CRS	Rwy Ldg	7822
Chan 59	322°	TDZE	439
(112.2)		Apt Elev	459

TACAN RWY 32L

SCOTT AFB/MIDAMERICA ST LOUIS (BLV)

⚠

ASR

For inop ALS, increase S-32L Cat C/D/E visibility to 1½ SM.


ALS-1

ⓐ


1

MISSED APPROACH: Climb to 1500 then climbing left turn to 2400 on SKE R-142 to WOMUG/14.1 DME and hold.

ATIS 128.7 256.7	ST LOUIS APP CON 125.2 281.5	SCOTT TOWER 128.25 253.5	GND CON 119.2 275.8
---------------------	---------------------------------	-----------------------------	------------------------



ELEV 459	D	TDZE 439
----------	---	----------



1500	2400	WOMUG SKE 14.1	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 50).			WOMUG SKE 14.1
↑	SKE R-142					
		CUMAB SKE 5				
		ZAVGU SKE 0.7				
		1800				
		1.4 NM	3 NM	9.1 NM		
CATEGORY	A	B	C	D	E	
S-32L	920/24	481 (500-½)	920/50	481 (500-1)	920/60	481 (500-1½)
CIRCLING	1000-1	1120-1	1240-2¼	1240-2½	1240-2¾	781 (800-2¾)
	541 (600-1)	661 (700-1)	781 (800-2¼)	781 (800-2½)	781 (800-2¾)	