

RNAV (GPS) PRM Y RWY 22R
(CLOSE PARALLEL)

DETROIT METRO WAYNE COUNTY (DTW)


WAAS CH 42939 W22B	APP CRS 213°	Rwy Ldg 10000 TDZE 642 Apt Elev 645
--	------------------------	--

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Use of FD or AP providing RNAV track guidance required during simultaneous operations. Simultaneous approach authorized. Dual VHF comm required. See additional requirements on AAUP.




MISSED APPROACH: Climb to 1100 then climbing right turn to 4000 direct DOHNT and hold.


D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 135.0 317.725 PRM 127.05	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
-------------------	---------------------------------	--	---	--------------------	-------



1100	4000	DOHNT	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).
------	------	-------	--



CATEGORY		A	B	C	D
LPV	DA	892/24 250 (300-½)			
INAV/ VNAV	DA	1050/45 408 (500-¾)			



DETROIT, MICHIGAN
Orig 10NOV16

42°13'N-83°21'W

DETROIT METRO WAYNE COUNTY (DTW)

RNAV (GPS) PRM Y RWY 22R (CLOSE PARALLEL)