

|                                        |                        |                                                                |
|----------------------------------------|------------------------|----------------------------------------------------------------|
| WAAS<br>CH <b>99601</b><br><b>W22A</b> | APP CRS<br><b>216°</b> | Rwy Ldg <b>12003</b><br>TDZE <b>637</b><br>Apt Elev <b>645</b> |
|----------------------------------------|------------------------|----------------------------------------------------------------|

RNAV (GPS) Z RWY 22L  
DETROIT METRO WAYNE COUNTY (DTW)

RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C (14°F) or above 54°C (130°F). Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cat C/D visibility to 1 1/2 SM. #RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

**MISSED APPROACH:**  
Climb to 4000 direct  
HWLER and hold.

|                          |                                        |                                       |                                                                             |                           |       |
|--------------------------|----------------------------------------|---------------------------------------|-----------------------------------------------------------------------------|---------------------------|-------|
| D-ATIS<br><b>133.675</b> | DETROIT APP CON<br><b>124.05 284.0</b> | METRO TOWER<br><b>128.125 317.725</b> | GND CON<br><b>121.8 (NW) 119.45 (NE)</b><br><b>132.725 (SW) 119.25 (SE)</b> | CLNC DEL<br><b>120.65</b> | CPDLC |
|--------------------------|----------------------------------------|---------------------------------------|-----------------------------------------------------------------------------|---------------------------|-------|

