

WAAS CH 50544 W32A	APP CRS 320°	Rwy Ldg TDZE 2587 Apt Elev 2592
--	------------------------	---

RNAV (GPS) RWY 32

DICKINSON/THEODORE ROOSEVELT RGNL (DIK)

RNP APCH - GPS.

▼


▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cat C/D visibility to ⅔ SM.

MALSR

MISSED APPROACH: Climb to 4400 direct LEGRY and hold.

ASOS 118.375	MINNEAPOLIS CENTER 124.25 236.825	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------------



4400

LEGRY

ELEV 2592

D

TDZE 2587

HIRL Rwy 14-32 0

MIRL Rwy 7-25 0

REIL Rws 7, 14 and 25 0

CATEGORY	A	B	C	D
LPV DA	2787-½		200 (200-½)	
LNAV/VNAV DA	2837-½		250 (300-½)	
LNAV MDA	2880-½		293 (300-½)	
CIRCLING	3060-1	468 (500-1)	3120-1½ 528 (600-1½)	3200-2 608 (700-2)