



WAAS CH 61111 W22A	APP CRS 219°	Rwy Ldg 8001 TDZE 31 Apt Elev 33
--	------------------------	---

RNAV (GPS) RWY 22

ELLINGTON (EFD)

RNP APCH.	MALSR	MISSED APPROACH: Climb to 500 then climbing left turn to 3100 direct WATFO and hold.
Circling NA west of Rwy 17R - 35L. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to RVR 4500, and LNAV Cats C/D/E visibility to RVR 5500.		

ATIS 135.575 269.9	HOUSTON APP CON 134.45 284.0	ELLINGTON TOWER 126.05 253.5	GND CON 121.6 275.8
------------------------------	--	--	-------------------------------



500	3100	WATFO	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 50).		
*LNAV only.			YAKUD 2.2 NM to RW22	WZDOM 2000	SEVSY 2000
			1 NM	1.2 NM	3.8 NM
CATEGORY	A	B	C	D	E
LPV	DA	231/18		200 (200-½)	
LNAV/VNAV	DA	341/24		310 (400-½)	
LNAV	MDA	400/24	369 (400-½)	400/35 369 (400-¾)	
CIRCLING	500-1		467 (500-1)	580-1½ 547 (600-1½)	640-2 607 (700-2) 700-2¼ 667 (700-2¼)