

WAAS
CH **62802**
W32A

APP CRS
320°

Rwy Ldg
TDZE **793**
Apt Elev **796**

RNAV (GPS) Y RWY 32

INDIANAPOLIS INTL (IND)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F).
DME/DME RNP-0.3 NA. **RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
-------------------------	--	----------------------------------	-------------------------	---------------------------------	-------

ELEV 796	D	TDZE 793
----------	----------	----------

HIRL all Rwys
TDZ/CL Rwys 5L and 5R

3000 KEADY	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).			
	BTTLR 2400		OZMOE 4500	
*LNAV only	*1 NM to RW32			
	1 NM	3.9 NM	8 NM	GP 3.00° TCH 53
CATEGORY	A	B	C	D
LPV DA	** 993/24 200 (200-½)			
LNAV/VNAV DA	1069/24 276 (300-½)			
LNAV MDA	1160/24	367 (400-½)	1160/35	367 (400-¾)
CIRCLING	1420-1	624 (700-1)	1420-1¾ 624 (700-1¾)	1560-2½ 764 (800-2½)

INDIANAPOLIS, INDIANA

Amdt 4A 17AUG17

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (GPS) Y RWY 32